

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau




(43) International Publication Date  
19 February 2004 (19.02.2004)

PCT

(10) International Publication Number  
**WO 2004/015730 A1**

- (51) International Patent Classification<sup>7</sup>: **H01H 9/06**
- (21) International Application Number:  
PCT/CA2003/000236
- (22) International Filing Date: 17 February 2003 (17.02.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
2,397,024 7 August 2002 (07.08.2002) CA
- (71) Applicant and  
(72) Inventor: **TURLEY, Edward, M.** [CA/CA]; 400 Bennett Avenue, Penticton, British Columbia V2A 2P6 (CA).
- (74) Agent: **SMITH, Paul**; Paul Smith Intellectual Property Law, Suite 330, 1508 West Broadway, Vancouver, British Columbia V6J 1W8 (CA).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SWITCH MECHANISM FOR REVERSIBLE GRINDER



(57) **Abstract:** A switch mechanism for use with reversible handheld power tools comprises a pair of switches that co-operate using abutment to restrict displacement of each switch according to the position of the other switch. In a tool having a dynamic brake and a series-wound motor, one of the switches has a false neutral position wherein a continuous current path is maintained between the tool motor and the dynamic brake when the second switch is moved from REVERSE or FORWARD to the neutral position.